


## 8 CHANNEL DVR



# OAR18C8MS1

8MP / 5MP / 4MP / 3MP / 1080P / 720P HD DVR



AHD/TVI/CVI  
CVBS/IP



4K Output



DDNS



Network



PTZ



Audio



Mic.



Smartphone



CMS



USB



Mouse



E-mail



# OAR18C8MS1


8MP / 5MP / 4MP / 3MP / 1080P / 720P HD DVR

## SPECIFICATIONS

Model	OAR18C8MS1
<b>Specifications</b>	
<b>System</b>	
Operating System	Embedded LINUX
<b>Video</b>	
Input	Analog: 8 CH (TVI/AHD: 8MP; TVI/AHD: 5MP; AHD/TVI/CVI: 4MP; AHD/TVI: 3MP; AHD/TVI/CVI: 1080P/720P; Analog: 960H) Analog+Network: 2 CH Analog+14 CH network(Max 8MP), 4 CH Analog+12 CH network(Max 8MP), 6 CH Analog+10 CH network(Max 8MP) Network: 32 CH network(Max 8MP)(Total incoming bandwidth ≤ 160M)
Input Interface	8 CH BNC
Signal Type	Analog/AHD/CVI/TVI 2.0/TVI 3.0/Network
Output	1 HDMI, 1 VGA
<b>Audio</b>	
Input	4 Channel RCA
Two-way Audio	No
Output	1 Channel RCA
<b>Alarm</b>	
Input	No
Output	No
Motion Detection	8 Channel (max 32 Channel in pure network mode)
Trigger Events	Recording, Email, Screen tips, Buzzer, Push notifications (motion detection)
Email Alarm	Send Image to designated E-mail id(s)
<b>PTZ</b>	
Interface	RS-485
Protocol	Pelco-D, Pelco-P
Baud Rate	110~921600
Address	0~255
<b>Display</b>	
VGA Output	Resolution: 1920 × 1080/60Hz, 1280 × 1024/60Hz
HDMI Output	Resolution: 3840×2160/30Hz, 2560×1440/30Hz, 1920 × 1080/60Hz, 1280 × 1024/60Hz
Display Split	36 Channel/25 Channel/16 Channel/9 Channel/8 Channel/4 Channel/1Channel
Privacy Masking	3 Rectangular Zones (Each camera)
OSD	Camera title, Time, Video loss, Alarm, Motion detection and Recording
<b>Recording</b>	
Video Compression	High/Standard Video Compression
Audio Compression	G.711u
Resolution	8MP(3840 × 2160), 5MP (2592 × 1944), 4MP(2560 × 1440), 3MP (2048 × 1536), 1080P (1920 × 1080), 720P (1280 × 720), 960H (P:960 × 576/N:960 × 480)
Record Rate	Analog:PAL:8MP (3840 × 2160 8 CH @8fps), 5MP (2592 × 1944 8 CH @12fps), 4MP (2560 × 1440 8 CH @15fps), 3MP (2048 × 1536 8 CH @18fps), 1080P (1920 × 1080 8 CH @25fps), 720P (1280 × 720 8 CH @25fps), 960H (960 × 576 8 CH @25fps) Pure IP(High Video Compression): PAL:4k (22 CH @25fps), 5MP (32 CH @25fps), 4MP (32 CH @25fps), 3MP (32 CH @25fps), 1080P (32 CH @25fps), 960P(32CH@25fps), 720P (32CH@25fps), D1(32 CH @25fps)
Record Mode	Manual\Scheduled\Motion Detection

<b>Playback &amp; Backup</b>	
Decode Capability	3CH 4K@30fps
Sync Playback	Pure Analog: 8CH 8M@8fps, 8CH 5M@12fps, 8CH 4M@15fps, 8CH 3M@18fps, 8CH 1080p@30fps Pure IPC: 3CH 4K@30fps, 4CH 5M@30fps, 6CH 4M@30fps, 6CH 3M@30fps, 9CH 1080P@30fps, 9CH 960P@30fps, 9CH 720P@30fps
Remote Playback	4 Channel / 1 Channel
Search Mode	ALL, Channel, Manual, Time, Date, Motion Detection
Playback Functions	Play, Pause, Stop, Fast play, Rewind, Digital Zoom, Full screen
Smartphone Playback	4 Channel
Backup Mode	USB Device (with format FAT 32)/Network
<b>Network</b>	
Interface	1 RJ45 10M/100M/1000M Adaptive Ethernet Interface
Network Functions	TCP/IP, HTTP, UPnP, DNS, NTP, SMTP, PPPoE, DHCP, FTP, DDNS, RTP, RTSP and RTCP
DDNS	Dyndns, changeip, no-ip, Oray, A-PRESS, MYQSEE, SKDDNS and SMART-EYES
Web Browser	IE8-11, Google Chrome (lower than Ver44), Firefox (lower than Ver53)
CMS Software	Supports Windows 7/ Windows 8/Windows 10
Extra Stream	D1/CIF(1~30fps)
Smartphone	iOS and Android
<b>Hard Disk Driver</b>	
Interface Type	1 SATA Interface
Capacity	1 SATA Hard Disk (2.5"/3.5" SATA, Up to 8TB)
<b>General</b>	
Language	English, Polish, Czech, Russian, Thai, Hebrew, Arabic, Bulgarian, Farisa German, French, Portuguese, Turkic, Spanish, Italian, Hungarian, Romanian, Korean, Dutch, Greek and Chinese
UTC Control	Yes
USB Interface	2 USB 2.0
Power consumption	DC 12V≤ 10W (Without Hard Disk)
Working Environment	-10~55 °C/10~90%
Dimension (W×D×H)	260*215*43(mm)
Weight	2.0 Kg. (Without HDD)

## DIMENSIONS



**OZONE SECUTECH PRIVATE LIMITED**

Operations Office : Plot No. 548, Udyog Vihar Phase V, Gurugram, Haryana, 122016

Email : [customercare@ozonesecutech.com](mailto:customercare@ozonesecutech.com) | Website : [www.ozonesecutech.com](http://www.ozonesecutech.com)